



MODEL #:	WATTAGE:	VOLTAGE:	KELVIN:	SIZE:
TECHNOLOGY:	ACCESSORIES:			
PROJECT:	NOTES:			
TYPE:	AREA:			

**FEATURES**

**PRODUCT IMAGE**


**APPLICATION**

- Ceiling
- Indoor
- Over Bed & Vanity
- Pendant



**LOCATION**

- Damp



**LIGHT PROPERTIES**

Available Kelvin Options:

2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT
---------------------	---------------------	------------------	---------------------	-------------------

**LED CHIPS USED**  
LG/NICHIA/SAMSUNG

**TESTED**  
LM80 AND  
LM82

**CRI**  
80+

**LIFE HOURS**  
50,000

WATTAGE	SOURCE LUMENS @40K	DELIVERED LUMENS
11	1276	1008
17	1972	1557
23	2668	2107
35	4060	3207
46	5336	4215

VOLTAGE
Standard: ND - 120V NON DIMMABLE
DV - 120V/277V NON DIMMABLE
TD - 120V TRIAC/ELV DIMMABLE
DVD - 120/277V 0-10V DIMMABLE



**ASL LIGHTING**

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2025 ASL Lighting Inc. All rights reserved.



Approval upon request

# STANDARD OPTIONS

## STANDARD BASE CONSTRUCTION

Steel Construction






## STANDARD LENS

Smooth White Acrylic

## STANDARD FINISH

Satin Nickel

## MODEL #CVBH ORDER FORM









WATTAGE *	VOLTAGE	KELVIN	SIZE
W11 - 11	Standard Voltage: ND - 120V NON DIMMABLE	 27K	L22 - L22 H5' D3 1/2
W17 - 17		 30K	L34 - L34 H5' D3 1/2
W23 - 23	DV - 120V/277V NON DIMMABLE	 35K	L46 - L46 H5' D3 1/2
W35 - 35	TD - 120V TRIAC/ELV DIMMABLE	 40K	
W46 - 46	DVD - 120/277V 0-10V DIMMABLE	 50K	

\* Up to 200W available on fixtures over 24".

# SPECIAL OPTIONS AVAILABLE (ONLY WHEN REQUIRED)

TECHNOLOGY	ACCESSORIES
EMG - Emergency EMGR - Emergency Remote OS - Occupancy Sensor OSCD - Occupancy Sensor Step Dimming PC - Photo Control	CCS - Cable Cord Suspension System CO - Convenience Outlet FBF - Front Baffle FUS - Fused PK1 - Canopy/Pendant Kit/1 ROD PK2 - Canopy/Pendant Kit/2 RODS PK3 - Canopy/Pendant Kit/3 RODS RS - Rocker Switch

### CUSTOM FINISH OPTIONS

 FGB Gloss Black	 FGBR Gloss Brass	 FGBZ Gloss Bronze	 FGW Gloss White	 FMB Matte Black
 FMBR Matte Brass	 FMW Matte White	 ORB Oil Rubbed Bronze		

Not seeing what you're looking for? Contact us to discuss more options.



## ASL LIGHTING

725 East state St. Trenton, NJ 08609 | info@aslightng.com | www.aslighting.com

TOLL FREE: 800-1101-1101 | LOCAL: 718-369-1100 | Shipping & Receiving: 322 Monmouth Street, Trenton, NJ, 08609

Specifications and dimensions are subject to change without notice / Consult your ASL lighten representative.

© Copyright © 2025 ASL Lighting Inc. All rights reserved.



Approval upon request